

Xerox® C310 Color Printer and Xerox® C315 Color Multifunction Printer



Work doesn't slow down, and your printer shouldn't either.



C310 Color Printer

C315 Color
Multifunction Printer

SYSTEM SPECIFICATION	XEROX C310 COLOR PRINTER	XEROX C315 COLOR MULTIFUNCTION PRINTER
PRINT SPEED (UP TO:)		
One-sided Speed¹ – Color Letter (8.5 x 11 in) A4 (210 x 297 mm)	35 ppm 33 ppm	
Two-sided Speed¹ – Color Letter (8.5 x 11 in) A4 (210 x 297 mm)	17 ppm 16 ppm	
One-sided Speed¹ – B&W Letter (8.5 x 11 in) A4 (210 x 297 mm)	35 ppm 33 ppm	
Two-sided Speed¹ – B&W Letter (8.5 x 11 in) A4 (210 x 297 mm)	17 ppm 16 ppm	
Monthly Duty Cycle² (Up To:) Pages Per Month	80,000	
Recommended Average Monthly Print Volume (Up To:) Pages Per Month	6,000	
Processor/Memory Clock Speed/Cores Memory	1 GHz Dual Core Processor with GPU 1GB RAM	1.2 GHz Quad Core Processor with GPU 2GB RAM
Connectivity Device Connectivity	Hi-Speed USB 2.0 (Type A- thumbdrive), Gigabit Ethernet, HI-Speed USB 2.0 (USB) (Type B), Wireless 802.11 b/g/n	
Imaging Technology	Color Laser	
PRINT AND COPY		
Print Resolution (Up To:)	1200 x 1200 dpi, 4800 Color Quality	
Copy Resolution (Up To:)	N/A	600 x 600 dpi
First-print-out Time (As Fast As:)	7.2 seconds color/6.7 seconds B&W	8.0 seconds color/7.9 seconds B&W
First-copy-out Time (As Fast As:)	N/A	9.1 seconds color/8.2 seconds B&W
Page Description Languages	PostScript® 3 Emulation, PCL® 6 Emulation, PCL 5, XPS, PDF v1.7 emulation, HTML, Direct Image	
Print Features³	One Touch UI, Print Quality, Normal, Secure, Saved and Sample Set Job Types, Duplex, Orientation, Collation, Print Job ID in Margins, Draft Mode, N-up, Booklet Layout, Watermark, Tray and Toner Status, Rotate Image 180 Degrees, Saved Settings, Earth Smart Settings	

Xerox C310 Color Printer and Xerox C315 Color Multifunction Printer

SYSTEM SPECIFICATION	XEROX C310 COLOR PRINTER	XEROX C315 COLOR MULTIFUNCTION PRINTER
MOBILE AND CLOUD READY		
Mobile Printing	Apple AirPrint, Mopria Print Service, Chromebook, Wi-Fi Direct®	
Mobile Scanning	Apple AirPrint, Mopria Scan Service	
Xerox® Workplace Suite and Xerox® Workplace Cloud	Yes	
Cloud Connectivity	Yes (via Xerox Print and Scan Experience)	
SCAN		
Destinations	N/A	Email, Front-side USB drive, FTP, Network or USB Connected Computer, Windows Network Folder
File Formats	N/A	TIFF, JPEG, PDF (non-searchable), Secure PDF, XPS
FAX		
Standard Features	N/A	MH/MR/MMR/JBIG/JBIG2/JPEG Compression, Auto Answer, Auto Redial, Auto Reduction, Broadcast Send, Junk Fax Filter, Fax Address Book, Fax Forward includes: Fax, Email, FTP, Network Folder, Called Number
PRINT DETAILS		
First-print-out Time – Color (As Fast As:)	7.2 seconds	8.0 seconds
First-print-out Time – B&W (As Fast As:)	6.7 seconds	7.9 seconds
Resolution (Up To:)	1200 x 1200 dpi, 4800 Color Quality	
Page Description Languages	PostScript® 3 Emulation, PCL® 6 Emulation, PCL 5, XPS, PDF v1.7 emulation, HTML, Direct Image	
Unprintable Page Margin	Print: 4.2 mm from each edge	Print: 4.2 mm from each edge; Copy: 3 mm from each edge
Print from USB	N/A	File Formats: Microsoft Office Formats (Word, Excel, PPT), PDF, HTML, XPS, Image Formats (JPEG, TIFF, GIF, BMP, PNG, PCX) Options available to configure prints from USB: paper source, print blank pages, collate, two-sided printing, paper saver orientation, separator sheets, paper saver, paper saver ordering
Print Driver Types/Operating Systems	Windows® 8, 8.1 Update 1, 10, 11, Windows Server® 2008 SP2 (32- and 64-bit), Windows Server 2008 R2 SP1, Windows Server 2012, Windows Server 2012 R2, Windows Server 2019, macOS 10.14, 10.15, 11, 12. For more information about supported Operating Systems, please visit our Drivers & Downloads page and specify your device at support.xerox.com	
Network Protocols	TCP/IP: HTTP/HTTPS, IPP, LPR/LDP, Raw Socket Printing/Port 9100, IPv4/IPv6, MS Web Services WSD-Print 802.1x, SNMP	
Font Capability	PCL6 89 scalable fonts, 2 bitmapped PS emulation 158 scalable fonts	
COPY DETAILS		
First-copy-out Time – Color (As Fast As:)	N/A	9.1 seconds
First-copy-out Time – B&W (As Fast As:)	N/A	8.2 seconds
Simplex Speed (Up To:)	N/A	35 Letter ppm/33 A4 ppm
Duplex Speed (Up To:)	N/A	17 Letter ppm/16 A4 ppm
Sides (Input:Output)	N/A	1:1, 1:2, 2:1, 2:2
Quantity	N/A	1-9,999
Concurrency	N/A	Yes (copy while printing)
Copy Features	N/A	Copy From Size; Copy To Size; Scale 25% to 400%; Darkness/Lightness; Sides 1:1, 1:2, 2:1, 2:2; Duplex; Collate; Sample Copy; Content Type – Text, Text/Photo, Photo, Graphics; Content Source – B&W Laser, Color Laser, Inkjet, Photo/Film, Magazine, Newspaper, Press, Other; Create Shortcut; Color Advanced Options Paper Setup; Advanced Imaging, Auto Center, Background Removal, Contrast, Mirror Image, Negative Image, Scan Edge to Edge, Shadow Detail, Sharpness, Color Balance, Color Dropout; Create Booklet; Cover Page Setup; Custom Job Build; Edge Erase; Header/Footer; Margin Shift; Overlay; Pages per Side – 2 pages per side, 4 pages per side; Separator Sheets – Between Pages, Between Copies, Between Jobs

Xerox C310 Color Printer and Xerox C315 Color Multifunction Printer

SYSTEM SPECIFICATION	XEROX C310 COLOR PRINTER	XEROX C315 COLOR MULTIFUNCTION PRINTER
SCAN DETAILS		
Technology	N/A	Color Flatbed Scanner with RADF, Contact Image Sensor (CIS)
Capability	N/A	RADF, up to 50 sheets of 20 lb bond/75 gsm, Color/B&W
Concurrency	N/A	Yes (scan while printing)
Input Speed – Color (Up To:)	N/A	32 ipm simplex/14 ipm duplex letter, 30 ipm simplex/13 ipm duplex A4
Input Speed – B&W (Up To:)	N/A	50 ipm simplex/23 ipm duplex letter, 47 ipm simplex/21 ipm duplex A4
Resolution	N/A	600 x 600 dpi
Resolution (Software Utilities) (dpi)	N/A	150 x 150, 200 x 200, 300 x 300, 400 x 400, 600 x 600
Maximum Scan Area (ADF) (in)	N/A	8.5 x 14 in
Maximum Scan Area (ADF) (mm)	N/A	216 x 355 mm
Maximum Scan Area (Platen) (in)	N/A	8.5 x 11.7 in
Maximum Scan Area (Platen) (mm)	N/A	216 x 297 mm
Media Weight (ADF)	N/A	52 to 120 gsm
Network Filing Protocol	N/A	FTP, SFTP, SMB, USB, Windows Network Folder
File Formats	N/A	TIFF, JPEG, PDF (non-searchable), Secure PDF, XPS
Scan Driver Compatibility	N/A	TWAIN, WIA, ICA
Scan File Compression Options	N/A	PDF – 1 bit – JBIG2, CCIT G4, Flate 8/24 bit – Flate, JPEG TIFF – 1 bit – CCITT G4 8/24 bit – Packbits, LZW JPG – 8/24 bit – JPEG
Supported Scan Destinations	N/A	Email, Front-side USB Drive, FTP, SFTP, Network or USB Connected Computer, Windows Network Folder
FAX DETAILS		
Fax Speed	N/A	33.6K bps
Memory	N/A	18MB
Resolution (dpi)	N/A	B&W standard 200 x 100 send, 200 x 100, 204 x 98 receive B&W fine 200 x 200 send, 200 x 200, 204 x 196 receive B&W superfine 300 x 300 send, 300 x 300, 204 x 391 receive B&W ultrafine 600 x 600 send, 600 x 600, 400 x 400, 408 x 391 receive Color fine 200 x 200 send, 200 x 200 receive Color superfine 300 x 300 send, 300 x 300, 400 x 400 receive
Compression	N/A	T.4 1D Modified Huffman Encoding T.4 2D Modified Read Encoding T.6 Modified Modified Read Encoding T.85 JBIG T.88 JBIG2 T.81 JPEG
Fax Features	N/A	Auto Answer, Auto Redial, Auto Reduction, Broadcast Send, Junk Fax Filter, Fax Address Book
Fax Forward Destinations	N/A	Fax – using one Fax Shortcut Email – using one Email Shortcut FTP – using one FTP Shortcut
DEVICE MANAGEMENT		
Device Management	Remote Console, Embedded Web Server, Xerox Easy Assist	
Xerox® CentreWare® Web Software	Yes	
SECURITY		
Security Protocols/Features	Digitally Signed Firmware Updates, Certificate Management, Secure Password Reset, TCP Connection Filtering, Port Filtering, Access Controls, Confidential Print, Non-Volatile Memory Wipe, Fax/Network Separation, Protected USB Ports, Auto-insertion of Sender's Email Address, Login Restrictions, TLS 1.3, Audit Log, Syslog	
WI-FI SECURITY		
Authentication and Encryption Methods	802.11 b/g/n, Infrastructure (BSS) Mode, WPA Personal TKIP PSK (63 char, 64 ASCII), WPA Enterprise, WPA3 Personal, WPA3 Enterprise, 802.1x; EAP-MD5, EAP-MSCHAPv2, EAP-TLS, EAP-TTLS (CHAPS/IMSCHASPv2/PAP), LEAP, PEAP	

Xerox C310 Color Printer and Xerox C315 Color Multifunction Printer

SYSTEM SPECIFICATION	XEROX C310 COLOR PRINTER	XEROX C315 COLOR MULTIFUNCTION PRINTER
PAPER HANDLING		
AUTOMATIC DOCUMENT FEEDER		
Type of ADF	N/A	Reversing Automatic Document Feeder (RADF)
Capacity (Up To:)	N/A	50 sheets of 20 lb bond/75 gsm stock; capacities will vary with different weight stocks
Minimum Media Size (in)	N/A	4.1 x 5.8 in
Minimum Media Size (mm)	N/A	A6 SEF (105 x 148 mm)
Maximum Media Size (in)	N/A	Legal (8.5 x 14 in)
Maximum Media Size (mm)	N/A	216 x 355 mm
Minimum Media Weight (gsm)	N/A	14 lb bond
Minimum Media Weight – Duplex (gsm)	N/A	52 gsm
Maximum Media Weight (gsm)	N/A	32 lb bond
Maximum Media Weight – Duplex (gsm)	N/A	120 gsm
PLATEN		
Maximum Media Size (in)	N/A	8.5 x 11.7 in
Maximum Media Size (mm)	N/A	216 x 297 mm
MANUAL FEED SLOT		
Standard/Optional	Standard	
Capacity	1 sheet of 20 lb bond/75 gsm	
Minimum Media Size (in)	3 x 5 in	
Minimum Media Size (mm)	76 x 127 mm	
Maximum Media Size (in)	Legal (8.5 x 14 in)	
Maximum Media Size (mm)	216 x 356 mm	
Minimum Media Weight (gsm)	60 gsm	
Minimum Media Weight – Duplex (gsm)	60 gsm	
Maximum Media Weight (gsm)	216 gsm	
Maximum Media Weight – Duplex (gsm)	105 gsm	
Media Types Supported	Light Paper, Plain Paper, Heavy Paper, Cardstock, Envelopes, Labels	
MAIN TRAY		
Standard/Optional	Standard	
Capacity (Up To:)	250 sheets of 20 lb bond/75 gsm	
Minimum Media Size (in)	3.8 x 5.8 in	
Minimum Media Size (mm)	98 x 148 mm	
Maximum Media Size (in)	Legal (8.5 x 14 in)	
Maximum Media Size (mm)	216 x 356 mm	
Minimum Media Weight (gsm)	60 gsm	
Minimum Media Weight – Duplex (gsm)	60 gsm	
Maximum Media Weight (gsm)	216 gsm	
Maximum Media Weight – Duplex (gsm)	105 gsm	
Media Types Supported	Light Paper, Plain Paper, Heavy Paper, Labels, Cardstock, Envelopes	

Xerox C310 Color Printer and Xerox C315 Color Multifunction Printer

SYSTEM SPECIFICATION	XEROX C310 COLOR PRINTER	XEROX C315 COLOR MULTIFUNCTION PRINTER
PAPER HANDLING (CONTINUED)		
550 PLUS 100 SHEET TRAY – 100 SHEET TRAY		
Standard/Optional	Optional – included with the 550 plus 100 Sheet Tray	
Capacity (Up To:)	100 sheets of 20 lb bond/75 gsm	
Minimum Media Size (in)	3 x 5 in	
Minimum Media Size (mm)	76 x 127 mm	
Maximum Media Size (in)	Legal (8.5 x 14 in)	
Maximum Media Size (mm)	216 x 356 mm	
Minimum Media Weight (gsm)	60 gsm	
Minimum Media Weight – Duplex (gsm)	60 gsm	
Maximum Media Weight (gsm)	176 gsm	
Maximum Media Weight – Duplex (gsm)	105 gsm	
Media Types Supported	Light Paper, Plain Paper, Heavy Paper, Labels, Cardstock, Envelopes	
550 PLUS 100 SHEET TRAY – 550 SHEET TRAY		
Standard/Optional	Optional – included with the 550 plus 100 Sheet Tray	
Capacity (Up To:)	550 sheets of 20 lb bond/75 gsm	
Minimum Media Size (in)	5.83 x 8.27 in	
Minimum Media Size (mm)	148 x 210 mm	
Maximum Media Size (in)	Legal (8.5 x 14 in)	
Maximum Media Size (mm)	216 x 356 mm	
Minimum Media Weight (gsm)	60 gsm	
Minimum Media Weight – Duplex (gsm)	60 gsm	
Maximum Media Weight (gsm)	176 gsm	
Maximum Media Weight – Duplex (gsm)	105 gsm	
Media Types Supported	Light Paper, Plain Paper, Heavy Paper, Labels, Cardstock	
STANDARD/MAXIMUM INPUT CAPACITY		
Standard Input Capacity	251	
Maximum Input Capacity	901	
OUTPUT CAPACITY		
Output Capacity	125	150

Xerox C310 Color Printer and Xerox C315 Color Multifunction Printer

SYSTEM SPECIFICATION		XEROX C310 COLOR PRINTER	XEROX C315 COLOR MULTIFUNCTION PRINTER
DEVICE SPECIFICATIONS			
ELECTRICAL REQUIREMENTS			
North America	100 to 127 volts (V) (100 – 110 Japan) at 47 to 53 hz or 57 to 63 hertz (HZ) nominal 90 to 140 volts (90 – 110 Japan), extreme		
Europe	220 to 240 volts (V) at 47 to 53 hz or 57 to 63 hertz (HZ) nominal (not available in all countries) 198 to 259 volts, extreme		
POWER CONSUMPTION			
Operation/Running – 110V	Simplex 530W; Duplex 360W		
Operation/Running – 220V	Simplex 530W; Duplex 360W		
Standby Mode – 110V	22W	26.2W	
Standby Mode – 220V	22W	26.2W	
Auto Off/Sleep Mode – 110V	1.61W	1.44W	
Auto Off/Sleep Mode – 220V	1.61W	1.44W	
Power Off Mode – 110V	0.2W		
Power Off Mode – 220V	0.2W		
Default Time to Sleep Mode	3 minutes		
Time to First Print from Sleep Mode	15 seconds	16 seconds	
Time to Ready from Off	42 seconds	49 seconds	
OPERATING ENVIRONMENT			
Required Temperature Range – Fahrenheit (storage)	50 to 90° F Shipping: -40 to 110° F		
Required Temperature Range – Fahrenheit (operating)	50 to 90° F		
Required Temperature Range – Celsius (storage)	10 to 32.2° C Shipping: -40 to 43.3° C		
Required Temperature Range – Celsius (operating)	10 to 32.2° C		
Required Relative Humidity	15% to 80% RH		
SOUND POWER LEVELS			
Sound Pressure Levels	Operating simplex b&w/col 49/50 dB(A) Operating duplex b&w/col 51/52 dB(A) Quiet mode simplex b&w/col 46/47 dB(A) Quiet mode duplex b&w/col 49/49 dB(A) Idle 15 dB(A)		Operating simplex b&w/col 52/52 dB(A) Operating duplex b&w/col 52/53 dB(A) Quiet mode simplex b&w/col 49/49 dB(A) Quiet mode duplex b&w/col 50/50 dB(A) Idle 15 dB(A)
Sound Power Levels	Operating simplex b&w/col 64/65 dB(A) Operating duplex b&w/col 65/66 dB(A) Quiet mode simplex b&w/col 61/62 dB(A) Quiet mode duplex b&w/col 63/64 dB(A) Idle 31 dB(A)		Operating simplex b&w/col 67/67 dB(A) Operating duplex b&w/col 67/67 dB(A) Quiet mode simplex b&w/col 63/63 dB(A) Quiet mode duplex b&w/col 64/65 dB(A) Idle 31 dB(A)
DIMENSIONS AND WEIGHTS			
ENGINES (UNPACKAGED)			
Width (in)	17.4 in		
Depth (in)	16.6 in	23.1 in	
Height (in)	12.1 in		18.2 in
Weight (lb)	46 lb		60 lb
Width (mm)	442 mm		
Depth (mm)	421 mm	588 mm	
Height (mm)	308 mm		462 mm
Weight (kg)	21 kg		27.1 kg

Xerox C310 Color Printer and Xerox C315 Color Multifunction Printer

SYSTEM SPECIFICATION	XEROX C310 COLOR PRINTER	XEROX C315 COLOR MULTIFUNCTION PRINTER
DIMENSIONS AND WEIGHTS (CONTINUED)		
550 PLUS 100 SHEET TRAY (UNPACKAGED)		
Width (in)	16.7 in	
Depth (in)	16.4 in	
Height (in)	5.2 in	
Weight (lb)	9.3 lb	
Width (mm)	424 mm	
Depth (mm)	416 mm	
Height (mm)	133 mm	
Weight (kg)	4.2 kg	
ENGINES (PACKAGED)		
Width (in)	19.5 in	22.0 in
Depth (in)	23.4 in	
Height (in)	15.8 in	22.4 in
Weight (lb)	52.3 lb	67.8 lb
Width (mm)	495 mm	558 mm
Depth (mm)	595 mm	594 mm
Height (mm)	402 mm	570 mm
Weight (kg)	23.8 kg	30.8 kg
550 PLUS 100 SHEET TRAY (PACKAGED)		
Width (in)	8.6 in	
Depth (in)	20.0 in	
Height (in)	18.8 in	
Weight (lb)	11.45 lb	
Width (mm)	218 mm	
Depth (mm)	508 mm	
Height (mm)	478 mm	
Weight (kg)	5.2 kg	
INSTALLATION CONSIDERATIONS		
Clear area around the device is necessary for access and ventilation. The below table shows the area needed on each side for correct installation.		
Top	10 in/254 mm	12 in/305 mm
Rear	4 in/101.6 mm	
Left	3 in/76.2 mm	
Right	3 in/76.2 mm	
Front	3 in/76.2 mm	
SYSTEM CERTIFICATION/REGULATORY COMPLIANCE		
Certifications	To view the latest list of certifications, go to xerox.com/OfficeCertifications	
WHAT'S IN THE BOX		
All items contained in the box	C310 Color Printer Power Cord Installation Guide Product Safety Sheet Quick Use Guide Software and Documentation CD Pre-installed Starter Capacity CMY Print Cartridges: 1,000 page capacity ⁴ ; K cartridge: 1,500 page capacity ⁴	C315 Color Multifunction Printer Power Cord Installation Guide Product Safety Sheet Quick Use Guide Software and Documentation CD Pre-installed Starter Capacity CMY Print Cartridges: 1,000 page capacity ⁴ ; K cartridge: 1,500 page capacity ⁴

Xerox C310 Color Printer and Xerox C315 Color Multifunction Printer

SUPPLIES AND ACCESSORIES	XEROX C310	XEROX C315
SUPPLIES – NORTH AMERICA AND EUROPE*		
Genuine Xerox Black Standard Capacity Toner Cartridge, Xerox C310/C315 Color Printer/Multifunction (3,000 Pages) ⁴	006R04356	
Genuine Xerox Cyan Standard Capacity Toner Cartridge, Xerox C310/C315 Color Printer/Multifunction (2,000 Pages) ⁴	006R04357	
Genuine Xerox Magenta Standard Capacity Toner Cartridge, Xerox C310/C315 Color Printer/Multifunction (2,000 Pages) ⁴	006R04358	
Genuine Xerox Yellow Standard Capacity Toner Cartridge, Xerox C310/C315 Color Printer/Multifunction (2,000 Pages) ⁴	006R04359	
Genuine Xerox Black High Capacity Toner Cartridge, Xerox C310/C315 Color Printer/Multifunction (8,000 Pages) ⁴	006R04364	
Genuine Xerox Cyan High Capacity Toner Cartridge, Xerox C310/C315 Color Printer/Multifunction (5,500 Pages) ⁴	006R04365	
Genuine Xerox Magenta High Capacity Toner Cartridge, Xerox C310/C315 Color Printer/Multifunction (5,500 Pages) ⁴	006R04366	
Genuine Xerox Yellow High Capacity Toner Cartridge, Xerox C310/C315 Color Printer/Multifunction (5,500 Pages) ⁴	006R04367	
Genuine Xerox Waste Toner Bottle, Xerox C310/C315 Color Printer/Multifunction (25,000 Pages)	008R13325	
Genuine Xerox Black Imaging Kit, Xerox C310/C315 Color Printer/Multifunction (125,000 Pages) ⁵	013R00689	
Genuine Xerox Color Imaging Kit (CMYK), Xerox C310/C315 Color Printer/Multifunction (125,000 Pages) ⁵	013R00692	
SUPPLIES – ALL OTHER REGIONS		
Genuine Xerox Black Standard Capacity Toner Cartridge, Xerox C310/C315 Color Printer/Multifunction (3,000 Pages) ⁴	006R04360	
Genuine Xerox Cyan Standard Capacity Toner Cartridge, Xerox C310/C315 Color Printer/Multifunction (2,000 Pages) ⁴	006R04361	
Genuine Xerox Magenta Standard Capacity Toner Cartridge, Xerox C310/C315 Color Printer/Multifunction (2,000 Pages) ⁴	006R04362	
Genuine Xerox Yellow Standard Capacity Toner Cartridge, Xerox C310/C315 Color Printer/Multifunction (2,000 Pages) ⁴	006R04363	
Genuine Xerox Black High Capacity Toner Cartridge, Xerox C310/C315 Color Printer/Multifunction (8,000 Pages) ⁴	006R04368	
Genuine Xerox Cyan High Capacity Toner Cartridge, Xerox C310/C315 Color Printer/Multifunction (5,500 Pages) ⁴	006R04369	
Genuine Xerox Magenta High Capacity Toner Cartridge, Xerox C310/C315 Color Printer/Multifunction (5,500 Pages) ⁴	006R04370	
Genuine Xerox Yellow High Capacity Toner Cartridge, Xerox C310/C315 Color Printer/Multifunction (5,500 Pages) ⁴	006R04371	
Genuine Xerox Waste Toner Bottle, Xerox C310/C315 Color Printer/Multifunction (25,000 Pages)	008R13325	
Genuine Xerox Black Imaging Kit, Xerox C310/C315 Color Printer/Multifunction (125,000 Pages) ⁵	013R00689	
Genuine Xerox Color Imaging Kit (CMYK), Xerox C310/C315 Color Printer/Multifunction (125,000 Pages) ⁵	013R00692	
OPTIONAL ACCESSORIES		
550 plus 100 Sheet Tray	497N07995	

* North America (NA): U.S., Canada

Europe (XE): U.K., France, Germany, Spain, Italy, Netherlands, Belgium, Norway, Sweden, Finland, Denmark, Iceland, Luxembourg, Austria, Switzerland, Portugal, Ireland Andorra, Azores, Corsica, Greenland, Iceland, Lichtenstein, Luxembourg, Madeira, San Marino

¹ Declared print speed in accordance with ISO/IEC 24734.

² Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

³ Some functionality may require software update from xerox.com available Q4 2021 (C310 only).

⁴ Average standard pages. Declared yield in accordance with ISO/IEC 19798. Yield will vary based on image, area coverage and print mode.

⁵ Approximate pages. Declared yield will vary depending on job run length and media size/orientation and print mode. For more information, visit office.xerox.com/latest/SUPGL-01.PDF C315 will become available early 2022.

For more information, visit us at xerox.com/office.

Xerox® C410 Color Printer



Work doesn't slow down,
and your printer shouldn't either.

PRINT SPEED (UP TO:)	
One-sided Speed¹	Color: Up to 42/40 ppm Letter/A4; Black-and-White: Up to 42/40 ppm Letter/A4
Two-sided Speed¹	Color: Up to 21/20 ppm Letter/A4; Black-and-White: Up to 21/20 ppm Letter/A4
Monthly Duty Cycle² (Up To:) Pages Per Month	125,000
Recommended Average Monthly Print Volume (Up To:) Pages Per Month	10,000
Processor/Memory/Storage Clock Speed/Cores Memory/Storage	1 GHz Dual Core Processor 1GB RAM 8GB eMMC/ Optional: 500+GB HDD
Connectivity Device Connectivity	Hi-Speed USB 2.0 (Type A), Hi-Speed USB (Type B) Gigabit Ethernet/ Optional: Wireless Network Adapter (802.11 b/g/n/ac)
Imaging Technology	Color Laser
PRINT	
Print Resolution (Up To:)	1200 x 1200 dpi, 4800 Color Quality
First-Print-Out Time (As Fast As:)	As fast as 6.4 seconds color/6.1 seconds black-and-white
Page Description Languages	PostScript® 3 Emulation, PCL® 6 Emulation, PCL 5 Emulation, PDF v1.7 Emulation, Direct Image
Print Features	One Touch UI, Print Quality, Normal, Secure, Saved and Sample Set Job Types, Duplex, Orientation, Collation, Print Job ID in Margins, Draft Mode, N-up, Booklet Layout, Watermark, Tray and Toner Status, Rotate Image 180 Degrees, Saved Settings, Earth Smart Settings
MOBILE AND CLOUD READY	
Mobile Printing	Apple AirPrint, Mopria Print Service, Chromebook, Wi-Fi Direct ^{®3}
Xerox® Workplace Suite and Xerox® Workplace Cloud	Optional: Xerox Workplace Cloud and Suite is the complete print management platform for security, cost control and mobility delivering workflow productivity to office and hybrid workers. Available as an on-premises version (Workplace Suite) or a cloud-based (Workplace Cloud) it provides the ultimate flexibility in freeing up IT teams time to focus on core business priorities. (Select models may require additional optional equipment to enable.)
Cloud Connectivity	Yes (via Xerox Print and Scan Experience)

Xerox C410 Color Printer

PRINT DETAILS	
First-Print-Out Time – Color (As Fast As:)	6.4 seconds
First-Print-Out Time – B&W (As Fast As:)	6.1 seconds
Resolution (Up To:)	1200 x 1200 dpi, 4800 Color Quality
Page Description Languages	PostScript® 3 Emulation, PCL® 6 Emulation, PCL 5 Emulation, PDF v1.7 Emulation, Direct Image
Unprintable Page Margin	Print: 4.2 mm from each edge
Print from USB	Yes. Documents; PDF, HTML, XPS, Microsoft file formats (.doc, .docx, .xls, .xlsx, .ppt, .pptx) Images: .dcm, .gif, .JPEG (.jpg), .bmp, .pcx, .TIFF (.tif), .png
Print Driver Types/Operating Systems	Windows® 11, Windows® 10, Windows Server 2022, Windows Server 2019, Windows Server 2016, Windows Server 2012 R2, Windows Server 2012, macOS 13.x, macOS 12.x, macOS 11.x. Microsoft Universal Print. For the latest information about supported Operating Systems, please visit our Drivers & Downloads page and specify your device at support.xerox.com .
Network Protocols	TCP/IP: HTTP/HTTPS, IPP, LPR/LDP, Raw Socket Printing/Port 9100, IPv4/IPv6, MS Web Services WSD-Print, 802.1x, SNMP, ThinPrint, Universal Print, Bonjour
Font Capability	PCL6 89 scalable fonts, 2 bitmapped PS emulation 158 scalable fonts
DEVICE MANAGEMENT	
Device Management	Xerox Easy Assist, Remote Operator Panel, Embedded Web Server
Xerox® CentreWare® Web Software	Yes
SECURITY	
Security Protocols/Features	Digitally Signed Firmware Updates, Trusted Platform Module (TPM), TLS 1.3, FIPS 140-2, Certificate Management, Secure Password Reset, TCP Connection Filtering, Port Filtering, Access Controls, Confidential Print, Non-Volatile Memory Wipe, Protected USB Ports, IPsec, Image Overwrite ⁴
WI-FI SECURITY (REQUIRES WIRELESS NETWORK ADAPTER)	
Authentication and Encryption Methods	Infrastructure (BSS) Mode, WEP Encryption (64 & 128 bit keys), WPA2/WPA Personal AES PSK, WPA2-Personal, WPA3 Support, 802.1x; EAP-MD5, EAP-MSCHAPv2, EAP-TLS, EAP-TTLS (CHAP/MSCHAP/MSCHAPv2/PAP), LEAP, PEAP
PAPER HANDLING	
MANUAL FEED SLOT	
Standard/Optional	Standard
Capacity	1 sheet
Minimum Media Size (in)	3 x 5 in
Minimum Media Size (mm)	76 x 127 mm
Maximum Media Size (in)	Legal (8.5 x 14 in)
Maximum Media Size (mm)	216 x 356 mm
Minimum Media Weight (gsm)	60 gsm
Minimum Media Weight – Duplex (gsm)	60 gsm
Maximum Media Weight (gsm)	200 gsm
Maximum Media Weight – Duplex (gsm)	105 gsm
Media Types Supported	Plain Paper, Light Paper, Heavy Paper, Letterhead, Cardstock, Recycled, Bond, Labels, Glossy, Vinyl, Pre-Printed, Envelope, Colored Paper, Rough Cotton, Custom
MAIN TRAY	
Standard/Optional	Standard
Capacity (Up To:)	250 sheets of 20 lb bond/75 gsm
Minimum Media Size (in)	3.9 x 5.8 in
Minimum Media Size (mm)	98 x 148 mm
Maximum Media Size (in)	Legal (8.5 x 14 in)
Maximum Media Size (mm)	216 x 356 mm
Minimum Media Weight (gsm)	60 gsm
Minimum Media Weight – Duplex (gsm)	60 gsm
Maximum Media Weight (gsm)	200 gsm
Maximum Media Weight – Duplex (gsm)	105 gsm
Media Types Supported	Plain Paper, Light Paper, Heavy Paper, Letterhead, Cardstock, Recycled, Bond, Labels, Glossy, Vinyl, Pre-Printed, Envelope, Colored Paper, Rough Cotton, Custom

Xerox C410 Color Printer

OPTIONAL 550+100-SHEET TRAY (INCLUDES 550-SHEETS STANDARD CAPACITY AND ADDITIONAL 100-SHEET BYPASS TRAY)	
550+100-SHEET TRAY – 100-SHEET BYPASS TRAY	
Capacity (Up To:)	100 sheets of 20 lb bond/75 gsm
Minimum Media Size (in)	3 x 5 in
Minimum Media Size (mm)	76 x 127 mm
Maximum Media Size (in)	Legal (8.5 x 14 in)
Maximum Media Size (mm)	216 x 356 mm
Minimum Media Weight (gsm)	60 gsm
Minimum Media Weight – Duplex (gsm)	60 gsm
Maximum Media Weight (gsm)	176 gsm
Maximum Media Weight – Duplex (gsm)	105 gsm
Media Types Supported	Plain Paper, Light Paper, Heavy Paper, Letterhead, Cardstock, Recycled, Bond, Labels, Glossy, Vinyl, Pre-Printed, Envelope, Colored Paper, Rough Cotton, Custom
550+100-SHEET TRAY – 550-SHEET TRAY	
Capacity (Up To:)	550 sheets of 20 lb bond/75 gsm
Minimum Media Size (in)	5.8 x 8.3 in
Minimum Media Size (mm)	148 x 210 mm
Maximum Media Size (in)	Legal (8.5 x 14 in)
Maximum Media Size (mm)	216 x 356 mm
Minimum Media Weight (gsm)	60 gsm
Minimum Media Weight – Duplex (gsm)	60 gsm
Maximum Media Weight (gsm)	176 gsm
Maximum Media Weight – Duplex (gsm)	105 gsm
Media Types Supported	Plain Paper, Light Paper, Heavy Paper, Letterhead, Cardstock, Recycled, Bond, Labels, Glossy, Vinyl, Pre-Printed, Colored Paper, Rough Cotton, Custom
OPTIONAL 550-SHEET TRAY (REQUIRES THE 550+100-SHEET TRAY)	
Capacity (Up To:)	550 sheets of 20 lb bond/75 gsm (Add up to 2 additional 550-sheet trays)
Minimum Media Size (in)	5.8 x 8.3 in
Minimum Media Size (mm)	148 x 210 mm
Maximum Media Size (in)	Legal (8.5 x 14 in)
Maximum Media Size (mm)	216 x 356 mm
Minimum Media Weight (gsm)	60 gsm
Minimum Media Weight – Duplex (gsm)	60 gsm
Maximum Media Weight (gsm)	176 gsm
Maximum Media Weight – Duplex (gsm)	105 gsm
Media Types Supported	Plain Paper, Light Paper, Heavy Paper, Letterhead, Cardstock, Recycled, Bond, Labels, Glossy, Vinyl, Pre-Printed, Envelope, Colored Paper, Rough Cotton, Custom
STANDARD/MAXIMUM INPUT CAPACITY	
Standard Input Capacity	251
Maximum Input Capacity	2001
OUTPUT CAPACITY	
Output Capacity	125

Xerox C410 Color Printer

DEVICE SPECIFICATIONS	
ELECTRICAL REQUIREMENTS	
North America	100 to 127 volts (V) (100 – 110 Japan) at 47 to 53 hz or 57 to 63 hertz (HZ) nominal 90 to 140 volts (90 – 110 Japan), extreme
Europe	220 to 240 volts (V) at 47 to 53 hz or 57 to 63 hertz (HZ) nominal (not available in all countries) 198 to 259 volts, extreme
POWER CONSUMPTION	
Operation/Running – 110V/220V	Simplex 574W; Duplex 383W
Standby Mode – 110V/220V	22W
Auto Off/Sleep Mode – 110V/220V	1.61W
Power Off Mode – 110V/220V	0.2W
Default Time to Sleep Mode	15 minutes
Time to First Print from Sleep Mode	15 seconds
Time to Ready from Off	42 seconds
OPERATING ENVIRONMENT	
Required Temperature Range – Fahrenheit (storage)	60 to 90° F Shipping: -40 to 104° F
Required Temperature Range – Fahrenheit (operating)	60 to 90° F
Required Temperature Range – Celsius (storage)	15 to 32° C Shipping: -40 to 40° C
Required Temperature Range – Celsius (operating)	15 to 32° C
Required Relative Humidity	8% to 80% RH
SOUND POWER LEVELS	
Sound Pressure Levels	Operating simplex b&w/col 51/52 dB(A) Operating duplex 53/54 dB(A) Quiet mode simplex 47/48 dB(A) Idle 14 dB(A)
Sound Power Levels	Operating simplex b&w/col 6.6/6.7 B(A) Operating duplex 6.7/6.8 B(A) Quiet mode simplex 6.2/6.2 B(A) Idle 3.1 B(A)

Xerox C410 Color Printer

DIMENSIONS AND WEIGHTS	
Printer (Packaged)	Width: 19.5 in/495 mm Depth: 23.4 in/595 mm Height: 15.8 in/402 mm Weight: 52.5 lb/23.9 kg
Printer (Unpackaged)	Width: 17.9 in/445 mm Depth: 16.6 in/423 mm Height: 12.5 in/318 mm Weight: 45.3 lb/20.6 kg
550-Sheet Tray (requires the 550+100-Sheet Tray) (Packaged)	Width: 8.6 in/218 mm Depth: 20.0 in/508 mm Height: 18.8 in/478 mm Weight: 11.45 lb/5.2 kg
550-Sheet Tray (requires the 550+100-Sheet Tray) (Unpackaged)	Width: 16.7 in/424 mm Depth: 16.4 in/416 mm Height: 5.2 in/133 mm Weight: 8.6 lb/3.9 kg
550+100-Sheet Tray (Packaged)	Width: 8.6 in/218 mm Depth: 20.0 in/508 mm Height: 18.8 in/478 mm Weight: 11.45 lb/5.2 kg
550+100-Sheet Tray (Unpackaged)	Width: 16.7 in/424 mm Depth: 16.4 in/416 mm Height: 5.2 in/133 mm Weight: 9.3 lb/4.2 kg
Printer Stand (Packaged)	Width: 20.7 in/525 mm Depth: 22.2 in/565 mm Height: 9.2 in/235 mm Weight: 37.7 lb/17.1 kg
Printer Stand (Unpackaged)	Width: 18.2 in/463 mm Depth: 20 in/510 mm Height: 17.3 in/440 mm Weight: 32.7 lb/14.8 kg
INSTALLATION CONSIDERATIONS	
Clear area around the device is necessary for access and ventilation. The below table shows the area needed on each side for correct installation.	
Top	10 in/254 mm
Rear	4 in/101.6 mm
Left	3 in/76.2 mm
Right	3 in/76.2 mm
Front	3 in/76.2 mm
SYSTEM CERTIFICATION/REGULATORY COMPLIANCE	
Certifications	To view the latest list of certifications, go to xerox.com/OfficeCertifications
WHAT'S IN THE BOX	
All items contained in the box	C410 Color Printer Power Cord Installation Guide Product Safety Sheet Quick Use Guide Software and Documentation CD Pre-installed Starter Capacity Print Cartridges: One of each (Cyan, Magenta, Yellow) 2,000 print capacity ³ ; Black cartridge: 2,400 print capacity ⁵

Xerox C410 Color Printer

SUPPLIES AND ACCESSORIES	NORTH AMERICA AND EUROPE*	ALL OTHER REGIONS
Genuine Xerox Black Standard Capacity Toner Cartridge, Xerox C410 Color Printer (2,400 Pages) ⁵	006R04677	006R04677
Genuine Xerox Cyan Standard Capacity Toner Cartridge, Xerox C410 Color Printer (2,000 Pages) ⁵	006R04678	006R04678
Genuine Xerox Magenta Standard Capacity Toner Cartridge, Xerox C410 Color Printer (2,000 Pages) ⁵	006R04679	006R04679
Genuine Xerox Yellow Standard Capacity Toner Cartridge, Xerox C410 Color Printer (2,000 Pages) ⁵	006R04680	006R04680
Genuine Xerox Black High Capacity Toner Cartridge, Xerox C410 Color Printer (10,500 Pages) ⁵	006R04685	006R04764
Genuine Xerox Cyan High Capacity Toner Cartridge, Xerox C410 Color Printer (7,000 Pages) ⁵	006R04686	006R04765
Genuine Xerox Magenta High Capacity Toner Cartridge, Xerox C410 Color Printer (7,000 Pages) ⁵	006R04687	006R04766
Genuine Xerox Yellow High Capacity Toner Cartridge, Xerox C410 Color Printer (7,000 Pages) ⁵	006R04688	006R04767
Genuine Xerox Waste Toner Bottle, Xerox C410 Color Printer (30,000 Pages)	008R13325	008R13325
Genuine Xerox Black Imaging Kit, Xerox C410 Color Printer (125,000 Pages) ⁶	013R00700	013R00700
Genuine Xerox Color Imaging Kit (CMYK), Xerox C410 Color Printer (125,000 Pages) ⁶	013R00701	013R00701
OPTIONAL ACCESSORIES		
550+100-Sheet Tray	097N02468	
550-Sheet Tray (requires the 550+100-Sheet Tray)	097N02465	
500+GB Hard Disk	097N02464	
Xerox Printer Stand	097S05244	
Wireless Network Adapter	097N02470	

* North America (NA): U.S., Canada

Europe (XE): U.K., France, Germany, Spain, Italy, Netherlands, Belgium, Norway, Sweden, Finland, Denmark, Iceland, Luxembourg, Austria, Switzerland, Portugal, Ireland Andorra, Azores, Corsica, Greenland, Iceland, Lichtenstein, Luxembourg, Madeira, San Marino

¹ Declared print speed in accordance with ISO/IEC 24734.

² Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

³ Requires Wireless Network Adapter

⁴ Requires 500+GB Hard Disk

⁵ Average standard pages. Declared yield in accordance with ISO/IEC 19798. Yield will vary based on image, area coverage and print mode.

⁶ Approximate pages. Declared yield will vary depending on job run length and media size/orientation and print mode. For more information, visit office.xerox.com/latest/SUPGL-01.PDF

Return spent imaging supplies through the Xerox® Green World Alliance® collection/reuse/recycling program. Visit xerox.com/About-Xerox/Recycling.

For more information, visit us at xerox.com/office.

Xerox® VersaLink® C500 Color Printer

VersaLink® C500 Color Printers are built on Xerox® ConnectKey® Technology.
For more information, go to www.ConnectKey.com.



SYSTEM SPECIFICATIONS	VERSALINK® C500
One-sided Speed¹ 8.5 x 11 in. A4/210 x 297 mm 8.5 x 14 in./216 x 356 mm	Up to 45 ppm color and black-and-white Up to 43 ppm color and black-and-white Up to 37 ppm color and black-and-white
Two-sided Speed¹ 8.5 x 11 in. A4/210 x 297 mm 8.5 x 14 in./216 x 356 mm	Up to 44 ppm color and black-and-white Up to 42 ppm color and black-and-white Up to 22 ppm color and black-and-white
Monthly Duty Cycle²	Up to 120,000 pages/month
Recommended Average Monthly Print Volume³	Up to 10,000 pages
Hard Drive	Optional 320 GB HDD
Processor	1.05 GHz ARM Dual-Core
Memory	2 GB
Connectivity	Ethernet 10/100/1000 Base-T, High-speed USB 3.0, Wi-Fi 802.11n and Wi-Fi Direct with optional Wi-Fi Kit (concurrent wired and wireless connections supported), NFC Tap-to-Pair
Controller Features	Configuration Cloning, Xerox Extensible Interface Platform®, Xerox® App Gallery App, Xerox® Standard Accounting Tool, Network Accounting Enabled, Role Based Permissions, Convenience Authentication Enabled, Online Support
User Interface Languages	English, French, Italian, German, Spanish, Brazilian Portuguese, Russian, Dutch, Swedish, Danish, Finnish, Norwegian, Greek, Turkish, Polish, Czech, Hungarian, Romanian, Catalan, Ukrainian, Croatian

Xerox® VersaLink® C500 Color Printer

DEVICE SPECIFICATIONS				
ELECTRICAL REQUIREMENTS				
North America	Voltage: 110-127V -10%/+6% Frequency: 50/60 Hz +/-3%, 12A			
Europe and Other Geographies	Voltage: 220-240V +/-10% Frequency: 50 Hz +/-3%, 8A			
POWER CONSUMPTION				
Continuous Printing ⁴	730 watts or less			
Ready/Standby Mode ⁴	74 watts or less			
Energy Saver/Sleep Mode ⁴	.9 watts or less			
OPERATING ENVIRONMENT				
Required Temperature Range (Storage)	32° to 95° F (0° to 35° C)			
Required Temperature Range (Operating)	50° to 90° F (10° to 32° C)			
Required Relative Humidity	15% to 85%			
Sound Power Levels Operating Standby	7.17 B(A) or less 4.9 B(A) or less			
Sound Pressure Levels Operating Standby	56.2 dB(A) or less 33.6 dB(A) or less			
Boot Time (from Off to UI Ready)	As fast as 52 seconds			
Warm-up Time (from Sleep to UI Ready)	As fast as 11 seconds			
DIMENSIONS AND WEIGHT (UNPACKAGED)	WIDTH	DEPTH	HEIGHT	WEIGHT
VersaLink® C500	16.9 in./427.4 mm	18.4 in./465.5 mm	17.5 in./443.4 mm	61 lb./27.6 kg
550-sheet Paper Tray	16.5 in./420 mm	18.3 in./464.5 mm	4.8 in./123 mm	4.1 lb./6.6 kg
High-Capacity Feeder	28.5 in./724.2 mm	30.4 in./772.1 mm	18.1 in./459 mm	43.4 lb./19.7 kg
Caster Base	28.5 in./724.2 mm	30.4 in./772.1 mm	3.5 in./90 mm	18.7 lb./8.5 kg
DIMENSIONS AND WEIGHT (PACKAGED)	WIDTH	DEPTH	HEIGHT	WEIGHT
VersaLink® C500	22.8 in./580 mm	25 in./634 mm	23.9 in./607 mm	75 lb./34 kg
550-sheet Paper Tray	21.1 in./535 mm	23 in./584 mm	9.8 in./248 mm	18.7 lb./8.5 kg
High-Capacity Feeder	22.4 in./568 mm	26.1 in./663 mm	28 in./711 mm	83.8 lb./38 kg
Caster Base	23 in./585 mm	24.4 in./619 mm	13 in./330 mm	39.7 lb./18 kg
CERTIFICATIONS				
To view the latest list of certifications, go to www.xerox.com/OfficeCertifications .				

Xerox® VersaLink® C500 Color Printer

PRINT	
First-Print-Out Time	As fast as 5.3 seconds color/5.0 seconds black-and-white
Print Resolution	Up to 1200 x 2400 dpi
Page Description Languages	PCL® 5e, 6 PDF XPS TIFF JPEG HP-GL Adobe® PostScript® 3™
Maximum Print Area	4 mm from edge of paper
Print Features	Application Defaults Banner Pages Enable/Disable Bi-directional Real-time Status Booklet Layout Color Adjustments (lightness, contrast, saturation, color balance) Color Correction Draft Mode Fit to New Paper Size Job Identification (Print ID or Banner, Print ID in margins on first page only or all pages) Job Monitoring (Client or Local User Interface) N-up Page Layout (up to 16 pages per sheet) Paper Selection by Attribute Personal Print Print Around Enable/Disable Print from USB Run Black Sample Set Saved Job Scaling Secure Print Skip Blank Pages Special Pages (exception page programming: covers, inserts, exceptions pages) Store and Recall Driver Settings Stored Jobs Deletion Two-sided Printing Watermark (predefined and custom) Earth Smart Driver Settings
Print from USB	Allows walk-up printing from Type A USB port Supports direct printing from computer via Type B USB port Supported file formats: PDF, JPEG, TIFF, XPS, PDF/A
Operating Systems	Windows® 7, 8, 8.1, 10 Windows Server 2008 SP2, Server 2008 R2 SP1, Server 2012, Server 2012 R2, Server 2016 macOS® 10.11, 10.12, 10.13 Citrix® Redhat® Enterprise Linux® Fedora Core IBM® AIX® HP-UX® Oracle® Solaris SUSE® SAP® Note: For information about supported versions for the above operating systems, please visit our Drivers & Downloads page and specify your device at www.support.xerox.com .
Fonts	PostScript fonts: 136 PCL fonts: 83

Xerox® VersaLink® C500 Color Printer

Xerox® Global Print Driver®	A truly universal print driver that lets IT administrators install, upgrade and manage Xerox® and non-Xerox® devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management.
Xerox® Pull Print Driver	Makes it easy for IT managers to qualify, deploy and manage all print devices using a single driver in a Pull Print environment. Uses a single queue and single driver. The Xerox® Pull Print Driver extends convenience across a broad range of printing assets. IT administrators no longer need to manage and configure multiple drivers. Used in conjunction with Equitrac Office®, Ysoft® SafeQ®, Pharos® and others.
MOBILE SOLUTIONS AND MOBILE DEVICE APPS	
Apple® AirPrint®	Print email, photos and important office documents directly from an Apple iPhone® or iPad® with no drivers to install and no cables to connect. With AirPrint, an iPhone or iPad automatically locates and connects to the AirPrint-enabled device over the office Wi-Fi network.
Mopria® Certified	ConnectKey® Technology-enabled print devices are Mopria® certified. Mopria® certification ensures you can print wirelessly from your Mopria® supported (Android) smart phone, tablet and other mobile devices instantly and easily.
Xerox® @printbyXerox App	@printbyXerox App is a free service that allows secure printing from any email-enabled device (computer, phone, tablet, iOS, Android™, Google® Chromebook™ and more) to a Xerox® printer or MFP using a single email address with no IT intervention. No training is needed. End-users simply send attachments to the email address and release them at the MFP panel.
Xerox® Print Services plug-in for Android™ (Free at Google Play™ Store)	The Xerox® Print Services plug-in for Android KitKat (4.4 or greater) devices streamline mobile printing without third-party apps or additional print drivers. You can easily print photos, web pages and documents when your mobile device is connected to printers or multifunction printers using a wireless network. A robust print option set includes two-sided printing, stapling and secure code release. A free download is available from the Google Play™ store.
Xerox® Easy Assist App	The Xerox® Easy Assist app simplifies installation, monitoring and management of your printer or MFP right from your mobile phone. It provides easy access to self-support services and real-time monitoring of printer performance. And, Xerox® Smart Start Software takes the guess work out of setup by automating the installation of the latest software for your printer or MFP on your computer – all without IT support – allowing you to be up and running quickly.
Xerox® Workplace Suite and Xerox® Workplace Cloud	Xerox® Workplace Suite is a modular set of workflows designed to save customers time and money by providing effective control over their print fleet, while enabling worker productivity and mobility through a set of robust workflows. Xerox enables ultimate customer flexibility by offering these capabilities in both an on-premises server version (Workplace Suite) and with a cloud based-version (Workplace Cloud) of this solution.
SOFTWARE SOLUTIONS	
Xerox® ConnectKey® Apps (Found at the Xerox® App Gallery)	Increase user productivity by simplifying and shortening everyday tasks. Unlike traditional software, ConnectKey® Apps do not require a dedicated server, PC or IT resource. Instead, simply download these lightweight, serverless ConnectKey® Apps to the ConnectKey® Technology-enabled device.

SECURITY

<p>Security Features</p>	<p>Access Controls AES 256-bit Encryption Audit Log Certificate Path Validation Certificate Revocation List (CRL)/Status Protocol (OCSP) Detection of External Program Falsification (XCP Plug-in) Cisco® Identity Services Engine (ISE) Integration Domain Filtering FIPS 140-2 Firmware Verification Immediate Disk Overwrite* IP Address Filtering IPsec Network Authentication Port Filtering Pre-installed Self-Signed Certificates Role Based Permissions Secure Print Security Certificate Management Smart Card Enablement (CAC/PIV/.NET) SNMPv3 Status Protocol (OCSP) TLS 1.3/SSL Trusted Platform Module (TPM)</p> <p>*Requires HDD/Productivity Kit</p>
---------------------------------	--

ACCOUNTING

XEROX® STANDARD ACCOUNTING/NETWORK ACCOUNTING (STANDARD)

<p>Tracking</p>	<p>Print usage</p>
<p>Accounting</p>	<p>Xerox® Standard Accounting Tool Up to 1,000 User Accounts without HDD Up to 9,999 User Accounts with HDD Up to 500 General Accounts</p> <p>Network Accounting (Job Based Accounting) Up to 1,000 User IDs; Up to 1,000 Account IDs without HDD Up to 60,000 User IDs; Up to 60,000 Account IDs with HDD Up to 14,000 Accounting Records (transactions)</p>
<p>Features</p>	<p>Administrator can manage the feature via the Embedded Web Server.</p>

ACCOUNTING OPTIONS – NETWORK ACCOUNTING (ALLOWS CENTRAL SERVER TO MANAGE ALL ACCOUNTING)

	<ul style="list-style-type: none"> Enhanced network accounting with up to the minute data on how the system is being used Comprehensive management and enterprise scale tracking and reporting of device usage Numerous solutions are available through Xerox Alliance Partners. For details visit www.xerox.com Security enhancements include simultaneous support for HTTP/HTTPS protocols Device requests account authentication from third party server enabling larger databases of users and accounts Accept Authentication Login at control panel and pass to third party Networking Account
--	--

PAPER HANDLING

BYPASS TRAY

<p>Capacity⁵</p>	<p>150 sheets</p>
<p>Sizes</p>	<p>Custom sizes: 3 x 5 in. to 8.5 x 14 in./76 x 127 mm to 216 x 356 mm</p>
<p>Weights One-sided: Two-sided:</p>	<p>16 lb. bond to 80 lb. cover/60 to 220 gsm 16 lb. bond to 65 lb. cover/60 to 176 gsm</p>

Xerox® VersaLink® C500 Color Printer

Types	Bond Plain Paper Cardstock Custom Envelopes Hole Punched Labels Letterhead Lightweight Cardstock Pre-Printed Recycled
TRAY 1	
Capacity⁵	550 sheets
Sizes	Custom sizes: 3 x 7.5 in. to 8.5 x 14 in./76 x 190 mm to 216 x 356 mm
Weights One-sided: Two-sided:	16 lb. bond to 80 lb. cover/60 to 220 gsm 16 lb. bond to 65 lb. cover/60 to 176 gsm
Types	Bond Plain Paper Cardstock Custom Hole Punched Labels Letterhead Lightweight Cardstock Heavyweight Cardstock Pre-Printed Recycled Envelope
UP TO FOUR ADDITIONAL TRAYS (OPTIONAL)	
Capacity⁵	550 sheets
Sizes	Custom sizes: 3 x 7.5 in. to 8.5 x 14 in./76 x 190 mm to 216 x 356 mm
Weights One-sided: Two-sided:	16 lb. bond to 80 lb. cover/60 to 220 gsm 16 lb. bond to 65 lb. cover/60 to 176 gsm
Types	Bond Plain Paper Cardstock Custom Hole Punched Labels Letterhead Lightweight Cardstock Heavyweight Cardstock Pre-Printed Recycled
HIGH-CAPACITY FEEDER (OPTIONAL)	
Capacity⁵	2,000 sheets
Sizes	Letter/A4
Weights One-sided: Two-sided:	16 lb. bond to 65 lb. cover/60 to 176 gsm 16 lb. bond to 65 lb. cover/60 to 176 gsm

Types	Bond Plain Paper Hole Punched Letterhead Lightweight Cardstock Pre-Printed Recycled
TOTAL CAPACITY	
Standard Device Capacity⁵	700 sheets
Total Device Capacity⁵	3,250 sheets
PAPER OUTPUT	
Output Capacity⁵	500 sheets
Automatic Two-sided Printing	Standard
DEVICE MANAGEMENT	
Network Protocols	TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, IPv4/IPv6, WSD LDAP Bonjour®/AirPrint™ Most protocols not in use can be disabled
Administrative Protocols	DHCP, SNMP, WINS, HTTP, HTTPS, TLS 1.3, SNTP, MDNS
REMOTE CONTROL PANEL	
	<ul style="list-style-type: none"> • Enables faster, more convenient technical support and user training • IT administrators and other authorized users can control the device remotely from a web page on any device • Remote user experience is identical to performing tasks directly at the device
XEROX® CENTREWARE® WEB SOFTWARE	
	<ul style="list-style-type: none"> • A web-based server application for network administrators that permits web browser-based device management from any workstation, whether running Windows or UNIX or any other operating system • Works with any SNMP-managed printer from any manufacturer • Provides help with device discovery and installations, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management
XEROX® EMBEDDED WEB SERVER – INTEGRATED DEVICE WEB PAGE	
Device Status	<ul style="list-style-type: none"> • Tray Status/Contents • Consumables Status • Billing/Usage • Quick Links • Online Support
Print Queue Viewing	Job print queue management — view and delete
Job Submission	Print-ready files (PS, PCL, PDF, XPS, JPEG)
Device Administration	Allows simple, remote installation setting of configuration options and management of the device
Browsers	Microsoft® Internet Explorer® Microsoft Edge™ Mozilla™ Firefox® Apple® Safari® Google Chrome™
REMOTE SERVICES	
Automated Meter Readings (AMR)	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time.
Automatic Supplies Replenishment (ASR)	Automatically orders supplies for Xerox® output devices based on actual usage, eliminating the need to manually manage supplies inventory.

Xerox® VersaLink® C500 Color Printer

WHAT'S IN THE BOX		
	VersaLink® C500 Color Printer Starter Capacity Print Cartridge: One of each (Cyan, Magenta, Yellow): 2,400 print capacity ⁶ , Black: 5,000 print capacity ⁶ Software and Documentation CD (Safety, Regulatory, Recycling and Disposal Guides, Print Drivers, and Warranty Statement) Installation Guide Quick Use Guides Power Cord	
SUPPLIES AND ACCESSORIES	QUANTITY	PART NUMBER
SUPPLIES		
Standard Capacity Toner Cartridges	Black: 5,000 standard pages ⁶ Cyan: 2,400 standard pages ⁶ Magenta: 2,400 standard pages ⁶ Yellow: 2,400 standard pages ⁶	106R03862 106R03859 106R03860 106R03861
High-Capacity Toner Cartridges	Black 12,100 standard pages ⁶ Cyan: 5,200 standard pages ⁶ Magenta: 5,200 standard pages ⁶ Yellow: 5,200 standard pages ⁶	106R03869 106R03863 106R03864 106R03865
Extra High-Capacity Toner Cartridges	Cyan: 9,000 standard pages ⁶ Magenta: 9,000 standard pages ⁶ Yellow: 9,000 standard pages ⁶	106R03866 106R03867 106R03868
ROUTINE MAINTENANCE ITEMS		
Drum Cartridges	Cyan: 40,000 pages ⁷ Magenta: 40,000 pages ⁷ Yellow: 40,000 pages ⁷ Black: 40,000 pages ⁷	108R01481 108R01482 108R01483 108R01484
Waste Cartridge	30,000 pages ⁷	108R01416
ACCESSORIES		
550-sheet Feeder		097S04949
2,000-sheet High Capacity Feeder (includes Caster Base)		097S04948
Cabinet (includes stabilisers)		097S04994
Caster Base		097S04954
Productivity Kit with 320 GB HDD		497K18360
Wireless Network Adapter (Wi-Fi Kit)		497K16750
External Card Reader/RFID Kit		497K18380

¹ Declared print speed in accordance with ISO/IEC 24734.

² Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

³ Recommended average throughput is not a minimum but is intended to cover a range of volumes for different environments.

⁴ Power states defined per ENERGY STAR® Program requirements for Imaging Equipment.

⁵ Paper capacities are based on 20 lb./75 gsm stock; capacities will vary with different weight stocks.

⁶ Average standard pages. Declared Yield in accordance with ISO/IEC19798. Yield will vary based on image, area coverage and print mode.

⁷ Approximate pages. Declared yield will vary depending on job run length, media size/orientation and machine speed. For more information visit: <https://www.office.xerox.com/latest/SUPGL-01.pdf>.

Return spent imaging supplies through the Xerox Green World Alliance collection/reuse/recycling program.

For more information, visit www.xerox.com/About-Xerox/Recycling.

For more information, visit us at www.xerox.com/Office.

Configurations vary by geography.

Xerox® VersaLink® C600 Color Printer

VersaLink® C600 Color Printers are built on Xerox® ConnectKey® Technology.
For more information, go to www.ConnectKey.com.



SYSTEM SPECIFICATIONS	VERSALINK® 600
One-sided Speed¹ 8.5 x 11 in. A4/210 x 297 mm 8.5 x 14 in./216 x 356 mm	Up to 55 ppm color and black-and-white Up to 53 ppm color and black-and-white Up to 45 ppm color and black-and-white
Two-sided Speed¹ 8.5 x 11 in. A4/210 x 297 mm 8.5 x 14 in./216 x 356 mm	Up to 52 ppm color and black-and-white Up to 50 ppm color and black-and-white Up to 26 ppm color and black-and-white
Monthly Duty Cycle²	Up to 120,000 pages/month
Recommended Average Monthly Print Volume³	Up to 17,000 pages
Hard Drive	Optional 320 GB HDD
Processor	1.05GHz ARM Dual-Core
Memory	2 GB
Connectivity	Ethernet 10/100/1000 Base-T, High-speed USB 3.0, Wi-Fi 802.11n and Wi-Fi Direct with optional Wi-Fi Kit (concurrent wired and wireless connections supported), NFC Tap-to-Pair
Controller Features	Configuration Cloning, Xerox Extensible Interface Platform®, Xerox® App Gallery App, Xerox® Standard Accounting Tool, Network Accounting Enabled, Role Based Permissions, Convenience Authentication Enabled, Online Support
User Interface Languages	English, French, Italian, German, Spanish, Brazilian Portuguese, Russian, Dutch, Swedish, Danish, Finnish, Norwegian, Greek, Turkish, Polish, Czech, Hungarian, Romanian, Catalan, Ukrainian, Croatian

DEVICE SPECIFICATIONS

ELECTRICAL REQUIREMENTS

North America	Voltage: 110-127V +/-10% Frequency: 50/60 Hz +/-3%, 12A
Europe and Other Geographies	Voltage: 220-240V +/- 10% Frequency: 50/60 Hz +/-3%, 8A

POWER CONSUMPTION

Continuous Printing⁴	800 watts or less
Ready/Standby Mode⁴	85 watts or less
Energy Saver/Sleep Mode⁴	0.7 watts or less

OPERATING ENVIRONMENT				
Required Temperature Range (Storage)	32° to 95° F (0° to 35° C)			
Required Temperature Range (Operating)	50° to 90° F (10° to 32° C)			
Required Relative Humidity	15% to 85%			
Sound Power Levels Operating Standby	7.27 B(A) or less 4.84 B(A) or less			
Sound Pressure Levels Operating Standby	57.4 dB(A) or less, 33.5 dB(A) or less			
Boot Time (from Off to UI Ready)	As fast as 52 seconds			
Warm-up Time (from Sleep to UI Ready)	As fast as 11 seconds			
DIMENSIONS AND WEIGHT (UNPACKAGED)	WIDTH	DEPTH	HEIGHT	WEIGHT
Base Unit	16.9 in./427.4 mm	18.4 in./465.5 mm	17.5 in./443.4 mm	64.8 lb./29.4 kg
Base Unit with Additional 550-sheet Tray	16.9 in./427.4 mm	18.4 in./465.5 mm	22.3 in./566.4 mm	79.4 lb./36 kg
Base Unit with High-Capacity Feeder	28.5 in./724.2 mm	30.4 in./772.1 mm	35.5 in./902.4 mm	108.2 lb./49.1 kg
Base Unit with High-Capacity Feeder and Finisher	28.5 in./724.2 mm	30.4 in./772.1 mm	44.2 in./1121 mm	123.2 lb./55.9 kg
Base Unit with High-Capacity Feeder and Mailbox	28.5 in./724.2 mm	30.4 in./772.1 mm	44.2 in./1121 mm	119.9 lb./54.4 kg
550-sheet Paper Tray	16.5 in./420 mm	18.3 in./464.5 mm	4.8 in./123 mm	4.1 lb./6.6 kg
High-Capacity Feeder (includes Caster Base)	28.5 in./724.2 mm	30.4 in./772.1 mm	18.1 in./459 mm	43.4 lb./19.7 kg
Cabinet (includes Caster Base)	28.5 in./724.2 mm	30.4 in./772.1 mm	13.2 in./336 mm	37 lb./16.6 kg
Caster Base	28.5 in./724.2 mm	30.4 in./772.1 mm	3.5 in./90 mm	18.7 lb./8.5 kg
Mailbox	17.7 in./450.8 mm	18.8 in./477.6 mm	9.8 in./248.0 mm	11.7 lb./5.3 kg
Finisher	17.7 in./450.8 mm	16.2 in./411.0 mm	9.8 in./248.0 mm	15 lb./6.8 kg
DIMENSIONS AND WEIGHT (PACKAGED)	WIDTH	DEPTH	HEIGHT	WEIGHT
Base Unit	22.8 in./580 mm	25 in./634 mm	23.9 in./607 mm	77.2 lb./35 kg
550-sheet Paper Tray	21.1 in./535 mm	23 in./584 mm	9.8 in./248 mm	18.7 lb./8.5 kg
High-Capacity Feeder (includes Caster Base)	22.4 in./568 mm	26.1 in./663 mm	28 in./711 mm	83.8 lb./38 kg
Cabinet (includes Caster Base)	23 in./584 mm	24.8 in./629 mm	23.5 in./597 mm	57.3 lb./28 kg
Caster Base	23 in./585 mm	24.4 in./619 mm	13 in./330 mm	39.7 lb./18 kg
Mailbox	22.6 in./573 mm	20.4 in./518 mm	15.2 in./386 mm	16.3 lb./7.8 kg
Finisher	22.6 in./573 mm	15.7 in./398 mm	15.2 in./386 mm	18.6 lb./8.8 kg
CERTIFICATIONS				
To view the latest list of certifications, go to www.xerox.com/OfficeCertifications .				

Xerox® VersaLink® C600 Color Printer

PRINT	
First-Print-Out Time	As fast as 5.1 seconds color/4.7 seconds black-and-white
Print Resolution	Up to 1200 x 2400 dpi
Page Description Languages	PCL® 5e, 6 PDF XPS TIFF JPEG HP-GL Adobe® PostScript® 3™
Maximum Print Area	4 mm from edge of paper
Print Features	Application Defaults Banner Pages Enable/Disable Bi-directional Real-time Status Booklet Layout Color Adjustments (lightness, contrast, saturation, color balance) Color Correction Draft Mode Fit to New Paper Size Job Identification (Print ID or Banner, Print ID in margins on first page only or all pages) Job Monitoring (Client or Local User Interface) N-up Page Layout (up to 16 pages per sheet) Paper Selection by Attribute Personal Print Print Around Enable/Disable Print from USB Run Black Sample Set Saved Job Scaling Secure Print Skip Blank Pages Special Pages (exception page programming covers, inserts, exceptions pages) Store and Recall Driver Settings Stored Jobs Deletion Two-sided Printing Watermark (predefined and custom) Earth Smart Driver Settings
Print from USB	Allows walk-up printing from Type A USB port Supports direct printing from computer via Type B USB port Supported file formats: PDF, JPEG, TIFF, XPS, PDF/A
Operating Systems	Windows® 7, 8, 8.1, 10 Windows Server 2008 SP2, Server 2008 R2 SP1, Server 2012, Server 2012 R2, Server 2016 macOS® 10.11, 10.12, 10.13 Citrix® Redhat® Enterprise Linux® Fedora Core IBM® AIX® HP-UX® Oracle® Solaris SUSE® SAP® Note: For information about supported versions for the above operating systems, please visit our Drivers & Downloads page and specify your device at www.support.xerox.com .
Fonts	PostScript fonts: 136 PCL fonts: 83

Xerox® VersaLink® C600 Color Printer

Xerox® Global Print Driver®	A truly universal print driver that lets IT administrators install, upgrade and manage Xerox® and non-Xerox® devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management.
Xerox® Pull Print Driver	Makes it easy for IT managers to qualify, deploy and manage all print devices using a single driver in a Pull Print environment. Uses a single queue and single driver. The Xerox® Pull Print Driver extends convenience across a broad range of printing assets. IT administrators no longer need to manage and configure multiple drivers. Used in conjunction with Equitrac Office®, Ysoft® SafeQ®, Pharos® and others.
MOBILE SOLUTIONS AND MOBILE DEVICE APPS	
Apple® AirPrint®	Print email, photos and important office documents directly from an Apple iPhone® or iPad® with no drivers to install and no cables to connect. With AirPrint, an iPhone or iPad automatically locates and connects to the AirPrint-enabled device over the office Wi-Fi network.
Mopria® Certified	ConnectKey® Technology-enabled print devices are Mopria® certified. Mopria® certification ensures you can print wirelessly from your Mopria® supported (Android) smart phone, tablet and other mobile devices instantly and easily.
Xerox® @printbyXerox	@printbyXerox App is a free service that allows secure printing from any email-enabled device (computer, phone, tablet, iOS, Android™, Google® Chromebook™ and more) to a Xerox® printer or MFP using a single email address with no IT intervention. No training is needed. End-users simply send attachments to the email address and release them at the MFP panel.
Xerox® Print Services plug-in for Android™ (Free at Google Play™ Store)	The Xerox® Print Services plug-in for Android KitKat (4.4 or greater) devices streamline mobile printing without third-party apps or additional print drivers. You can easily print photos, web pages and documents when your mobile device is connected to printers or multifunction printers using a wireless network. A robust print option set includes two-sided printing, stapling and secure code release. A free download is available from the Google Play™ store.
Xerox® Easy Assist App	The Xerox® Easy Assist app simplifies installation, monitoring and management of your printer or MFP right from your mobile phone. It provides easy access to self-support services and real-time monitoring of printer performance. And, Xerox® Smart Start Software takes the guess work out of setup by automating the installation of the latest software for your printer or MFP on your computer – all without IT support – allowing you to be up and running quickly.
Xerox® Workplace Suite and Xerox® Workplace Cloud	Xerox® Workplace Suite is a modular set of workflows designed to save customers time and money by providing effective control over their print fleet, while enabling worker productivity and mobility through a set of robust workflows. Xerox enables ultimate customer flexibility by offering these capabilities in both an on-premises server version (Workplace Suite) and with a cloud based-version (Workplace Cloud) of this solution.
SOFTWARE SOLUTIONS	
Xerox® ConnectKey® Apps (Found at the Xerox App Gallery)	Increase user productivity by simplifying and shortening everyday tasks. Unlike traditional software, ConnectKey® Apps do not require a dedicated server, PC or IT resource. Instead, simply download these lightweight, serverless ConnectKey® Apps to the ConnectKey® Technology-enabled device.

SECURITY	
Security Features	Access Controls AES 256-bit Encryption Audit Log Certificate Path Validation Certificate Revocation List (CRL)/Status Protocol (OCSP) Detection of External Program Falsification (XCP Plug-in) Cisco® Identity Services Engine (ISE) Integration Domain Filtering FIPS 140-2 Firmware Verification Immediate Disk Overwrite* IP Address Filtering IPsec Network Authentication Port Filtering Pre-installed Self-Signed Certificates Role Based Permissions Secure Print Security Certificate Management Smart Card Enablement (CAC/PIV/.NET) SNMPv3 Status Protocol (OCSP) TLS 1.3/SSL Trusted Platform Module (TPM) *Requires HDD/Productivity Kit
ACCOUNTING	
XEROX® STANDARD ACCOUNTING/NETWORK ACCOUNTING (STANDARD)	
Tracking	Print usage
Accounting	Xerox® Standard Accounting Tool Up to 1,000 User Accounts without HDD Up to 9,999 User Accounts with HDD Up to 500 General Accounts Network Accounting (Job Based Accounting) Up to 1,000 User IDs; Up to 1,000 Account IDs without HDD Up to 60,000 User IDs; Up to 60,000 Account IDs with HDD Up to 14,000 Accounting Records (transactions)
Features	<ul style="list-style-type: none"> Administrator can manage the feature via the Embedded Web Server.
ACCOUNTING OPTIONS – NETWORK ACCOUNTING (ALLOWS CENTRAL SERVER TO MANAGE ALL ACCOUNTING)	
	<ul style="list-style-type: none"> Enhanced network accounting with up to the minute data on how the system is being used Comprehensive management and enterprise scale tracking and reporting of device usage Numerous solutions are available through Xerox Alliance Partners. For details visit www.xerox.com Security enhancements include simultaneous support for HTTP/HTTPS protocols Device requests account authentication from third party server enabling larger databases of users and accounts Accept Authentication Login at control panel and pass to third party NetworkingAccount
PAPER HANDLING	
BYPASS TRAY	
Capacity⁵	150 sheets
Sizes	Custom sizes: 3 x 5 in. to 8.5 x 14 in./76 x 127 mm to 216 x 356 mm
Weights One-sided: Two-sided:	16 lb. bond to 80 lb. cover/60 to 220 gsm 16 lb. bond to 65 lb. cover/60 to 176 gsm

Xerox® VersaLink® C600 Color Printer

Types	Bond Plain Paper Cardstock Custom	Envelopes Hole Punched Labels Letterhead	Lightweight Cardstock Pre-Printed Recycled
TRAY 1			
Capacity⁴	550 sheets		
Sizes	Custom sizes: 3 x 7.5 in. to 8.5 x 14 in./76 x 190 mm to 216 x 356 mm		
Weights One-sided: Two-sided:	16 lb. bond to 80 lb. cover/60 to 220gsm 16 lb. bond to 65 lb. cover/60 to 176gsm		
Types	Bond Plain Paper Cardstock Custom	Hole Punched Labels Letterhead Lightweight Cardstock	Heavyweight Cardstock Pre-Printed Recycled
UP TO FOUR ADDITIONAL TRAYS			
Capacity⁵	550 sheets		
Sizes	Custom sizes: 3 x 7.5 in. to 8.5 x 14 in./76 x 190 mm to 216 x 356 mm		
Weights One-sided: Two-sided:	16 lb. bond to 80 lb. cover/60 to 220gsm 16 lb. bond to 65 lb. cover/60 to 176gsm		
Types	Bond Plain Paper Cardstock Custom	Hole Punched Labels Letterhead Lightweight Cardstock	Heavyweight Cardstock Pre-Printed Recycled
HIGH-CAPACITY FEEDER (ONLY ONE ADDITIONAL 550-SHEET TRAY CAN BE ADDED TO HIGH-CAPACITY FEEDER)			
Capacity⁵	2,000 sheets		
Sizes	Letter/A4		
Weights One-sided: Two-sided:	16 lb. bond to 65 lb. cover/60 to 176gsm 16 lb. bond to 65 lb. cover/60 to 176gsm		
Types	Bond Plain Paper Hole Punched	Letterhead Lightweight Cardstock Pre-Printed	Recycled
TOTAL CAPACITY			
Standard Device Capacity⁵	700 sheets		
Maximum Device Capacity⁵	3,250 sheets		
PAPER OUTPUT/FINISHING			
Capacity⁵	Up to 500 sheets		
Automatic Two-sided Printing	Standard		
FINISHER			
Capacity⁵	500-sheet tray, 50-sheet stapling		
MAILBOX			
Capacity⁵	Four 100-sheet bins		

DEVICE MANAGEMENT	
Network Protocols	TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, IPv4/IPv6, WSD LDAP Bonjour®/AirPrint™ Most protocols not in use can be disabled
Administrative Protocols	DHCP, SNMP, WINS, HTTP, HTTPS, TLS 1.3, SNTP, MDNS
REMOTE CONTROL PANEL	
	<ul style="list-style-type: none"> • Enables faster, more convenient technical support and user training • IT administrators and other authorized users can control the device remotely from a web page on any device • Remote user experience is identical to performing tasks directly at the device
XEROX® CENTREWARE® WEB SOFTWARE	
	<ul style="list-style-type: none"> • A web-based server application for network administrators that permits web browser-based device management from any workstation, whether running Windows or UNIX or any other operating system • Works with any SNMP-managed printer from any manufacturer • Provides help with device discovery and installations, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management
XEROX® EMBEDDED WEB SERVER – INTEGRATED DEVICE WEB PAGE	
Device Status	<ul style="list-style-type: none"> • Tray Status/Contents • Consumables Status • Billing/Usage • Quick Links • Online Support
Print Queue Viewing	Job print queue management — view and delete
Job Submission	Print-ready files (PS, PCL, PDF, XPS, JPEG)
Device Administration	Allows simple, remote installation setting of configuration options and management of the device
Browsers	Microsoft® Internet Explorer® Microsoft Edge™ Mozilla™ Firefox® Apple® Safari® Google Chrome™
REMOTE SERVICES	
Automated Meter Readings (AMR)	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time.
Automatic Supplies Replenishment (ASR)	Automatically orders supplies for Xerox® output devices based on actual usage, eliminating the need to manually manage supplies inventory.
WHAT'S IN THE BOX	
	VersaLink® C600 Color Printer Starter Capacity Print Cartridge: One of each (Cyan, Magenta, Yellow): 6,000 print capacity ⁶ , Black: 10,000 print capacity ⁶ Software and Documentation CD (Safety, Regulatory, Recycling and Disposal Guides, Print Drivers, and Warranty Statement) Installation Guide Quick Use Guides Power Cord

Xerox® VersaLink® C600 Color Printer

SUPPLIES AND ACCESSORIES	QUANTITY	PART NUMBER
SUPPLIES		
Standard Capacity Toner Cartridges	Black: 6,000 standard pages ⁶ Cyan: 6,000 standard pages ⁶ Magenta: 6,000 standard pages ⁶ Yellow: 6,000 standard pages ⁶	106R03899 106R03896 106R03897 106R03898
High-Capacity Toner Cartridges	Black: 12,200 standard pages ⁶ Cyan: 10,100 standard pages ⁶ Magenta: 10,100 standard pages ⁶ Yellow: 10,100 standard pages ⁶	106R03903 106R03900 106R03901 106R03902
Extra-High Capacity Toner Cartridges	Black: 16,900 standard pages ⁶ Cyan: 16,800 standard pages ⁶ Magenta: 16,800 standard pages ⁶ Yellow: 16,800 standard pages ⁶	106R03919 106R03916 106R03917 106R03918
ROUTINE MAINTENANCE ITEMS		
Drum Cartridges	Cyan: 40,000 pages ⁷ Magenta: 40,000 pages ⁷ Yellow: 40,000 pages ⁷ Black: 40,000 pages ⁷	108R01485 108R01486 108R01487 108R01488
Waste Cartridge	30,000 pages ⁷	108R01416
ACCESSORIES		
550-sheet Feeder		097S04949
2,000-sheet High-Capacity Feeder (includes Caster Base)		097S04948
Cabinet (includes stabilisers)		097S04994
Caster Base		097S04954
Finisher (500 sheets, 50-sheet stapler)		097S04952
4-Bin Mailbox (100 sheets per bin)		097S04953
Productivity Kit with 320 GB HDD		497K18360
Wireless Network Adapter (Wi-Fi Kit)		497K16750
External Card Reader/RFID Kit		497K18380

¹ Declared print speed in accordance with ISO/IEC 24734.

² Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

³ Recommended average throughput is not a minimum but is intended to cover a range of volumes for different environments.

⁴ Power states defined per ENERGY STAR® Program requirements for Imaging Equipment.

⁵ Paper capacities are based on 20 lb./75 gsm stock; capacities will vary with different weight stocks.

⁶ Average standard pages. Declared Yield in accordance with ISO/IEC19798. Yield will vary based on image, area coverage and print mode.

⁷ Approximate pages. Declared yield will vary depending on job run length, media size/orientation and machine speed. For more information visit: <https://www.office.xerox.com/latest/SUPGL-01.pdf>.

Return spent imaging supplies through the Xerox Green World Alliance collection/reuse/recycling program.

For more information, visit www.xerox.com/About-Xerox/Recycling.

For more information, visit us at www.xerox.com/Office.

Configurations vary by geography.